

Sanitary Mould-Stop

Technical information sheet

500ml / Item no.025502001 / EAN 4007955255024



Removes mould and mildew stains quickly and reliably from all washable surfaces. Ideally suited for silicone and tile joints as well as wash-resistant emulsion paints. The effective cleaning action restores hygienic cleanliness and ensures permanently well-maintained, visually clean surfaces.

- with active chlorine for immediate effect
- Gel formula for optimum effect even on vertical surfaces
- Bleaches and disinfects
- Use biocidal products with care. Always read the label and product information before use.

Area of application

Quickly removes mould and mildew stains from surfaces, joints and paintwork. With active chlorine and gel formula, also for vertical surfaces.

Processing

Carefully spray the infested surface from a distance of approx. 15 - 20 cm until a closed film forms. After approx. 15 minutes, remove the residue with a damp sponge or cloth and wipe thoroughly with water.

Consumption

approx. 50-75 ml/m²

Storage

Keep container tightly closed in a dark, cool and frost-free place. Keep out of the reach of children.

Notes

Protect surfaces not to be treated from splashes. Sensitive and coloured materials such as wallpaper, carpets, textiles, wood and metals can be discoloured on the surface. Discolouration may also occur on tiles with damaged glaze. Avoid contact with plants. A slight odour of chlorine develops during application, which can last for up to three days and can be reduced by sufficient ventilation or shock ventilation. Only dispose of empty containers for recycling. Dispose of product residues as hazardous waste. Do not allow to enter the sewage system or bodies of water.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.