



Silicone remover for the thorough removal of fresh and hardened silicone residues. Suitable for ceramic tiles, glass, enamel, metal and similar substrates. Works quickly, reliably removes residues and leaves a clean surface for new sealants or coatings.

- Gel formula - also for vertical surfaces
- Complete set: 150 ml silicone remover, 1 brush, 1 special sponge

### Area of application

decotric Silicone Remover removes silicone residues from tiles, glass, enamel and metal. Also ideal for vertical surfaces thanks to the gel formula.

### Processing

Cut out the silicone joint with a sharp knife. Shake the bottle well before use. Apply the silicone remover to the residue with a brush and leave to work for between 10 minutes and 6 hours. Remove the dissolved residue with the special sponge. Rinse the sponge thoroughly with household cleaner after every 1 metre of joint length. Then rinse the surface thoroughly with water. Repeat the application if there are heavy residues. Before re-grouting, thoroughly wipe the bonding surfaces dry with a clean cloth.

### Storage

Keep container tightly closed, dry and cool, but frost-free. Keep out of the reach of children.

### Notes

Wear suitable protective gloves during application. Before applying the product, test the resistance of the substrate on a small test area, as sensitive surfaces may be attacked. Treat metals only briefly and rinse thoroughly. Clean tools with water after use and only dispose of empty containers for recycling. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of liquid residues according to EWC waste code no. 08 01 12.

#### Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.