Crystal Finish - White mother-of-pearl

Technical information sheet

2,5l / Item number 017601074 / EAN 4044899176015



Decorative crystal effect paint with real glass beads for extraordinary surfaces. Solvent-free, easy to apply and effective in just one coat. Creates shimmering, textured wall designs indoors. Can be used on various substrates and applied in several coats. Ideal for creative room accents.

- Creative surface design in just one work step
- 750 ml for approx. 4 m²

Area of application

Crystal-Finish acrylic effect coating with glass beads - ideal for walls & ceilings. For wallpaper, plaster & masonry, creates elegant gloss effects.

Preparation

The substrate must be firm, dry, stable and free of separating agents (dust, formwork oil, etc.). Remove poorly adhering paint, wallpaper and loose plaster. Repair holes and cracks. Highly absorbent, sanding and chalking substrates must be primed with a deep penetrating primer. Even out differences in colour tone with a pigmented primer. Smooth renovation fleece provides an ideal substrate.

Processing

Crystal Finish is ready to use and can be applied crosswise with a brush. Several coats are possible. Crystal Finish Pearl can be tinted with max. 10% tinting concentrate in any colour variation for an individual colour design. For the same colour shade, mix different batches together before application. Allow to dry for approx. 8 hours after application. Do not apply below +5ºC substrate and room temperature. Clean tools with water immediately after use.

Storage

Keep container tightly closed and store in a cool but frost-free place. Keep out of the reach of children.

Notes

Only dispose of empty containers for recycling. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of liquid residues according to waste code no. EWC 08 01 12.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.