

## Metallic Paints

### Technical information sheet

750ml / Item no.017702001 / EAN 4007955177029 (Gold)  
750ml / Item no.018402001 / EAN 4007955184027 (Orient Gold)  
750ml / Item no.017802001 / EAN 4007955178026 (Silber)



Covering paint with an attractive metallic effect for high-quality wall and decorative designs. Suitable for wallpaper, plaster, polystyrene elements, masonry, stone and painted interior surfaces. Creates elegant, shimmering surfaces and stylish accents. Easy to apply and versatile in use.

- Very high opacity
- solvent-free
- Consumption: approx. 80-120 ml/m<sup>2</sup>

### Area of application

Opaque acrylic metal paint for modern living spaces - ideal for wallpaper, plaster & stone. Perfect for emphasising surfaces and decorative elements.

### Preparation

The substrate must be dry, stable and free of dust and grease. Repair holes and cracks. Prime highly absorbent, sanding or chalking substrates.

### Processing

Shake the container well before use. In order to achieve the most even pigment distribution possible, we recommend using a short-pile paint roller or a suitable spraying device when painting large areas. The metal effect colours should not be thinned or tinted, as this will reduce the metallic effect.

### Storage

Store tightly closed in a cool, dry place. Keep out of the reach of children.

### Notes

Long-term exposure to moisture can lead to discolouration of the painted surfaces. Mix different batches together before application. Do not apply below + 5 °C object and room temperature. Clean tools with water immediately after use. Only dispose of empty containers for recycling. Dried material residues can be disposed of with household waste or as construction site waste. EWC waste code no. 08 01 12.

#### Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.