



STOP Algae and Mould chlorine-free

Technical information sheet

BAuA-Reg.-Nr.: (D): N-117369

500ml / Item no.101810 / EAN 4016215101810



Ready-to-use, chlorine-free product for the removal and prevention of algae, mould and green deposits. Has a neutral odour and is suitable for indoor and outdoor use on walls, ceilings, floors and facades. Cleans reliably and also serves as an ideal substrate pre-treatment for subsequent coatings or impregnations. Easy to use and sustainably effective for permanently clean surfaces.

- chlorine-free
- Odourless
- Removes mould, algae and green deposits
- has a self-acting and preventive effect
- Use biocidal products with care. Always read the label and product information before use

Area of application

Mould remover against mould and algae for indoors and outdoors. Cleans walls, floors, roofs, tiles and stone, also suitable as a pre-treatment top inside.

Processing

Spray baufan Algae and Mould STOP directly onto the infested surface from a distance of approx. 15 - 20 cm and allow to take effect. The effect takes effect within 1 - 2 days. In the case of very heavy contamination, if there is no visual change to the treated surface, carry out a further treatment with baufan Algae and Mould STOP. Wash off any residues with clear water.

Consumption

50 - 100 ml/m² of thinner

Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least until: see batch label.

Notes

Processing temperature: +5 °C to +30 °C for material, ambient air and substrate Only use outdoors or in well-ventilated rooms. Avoid release into the environment. Dispose of contents/container to waste disposal according to local/regional/national regulations.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.