Mould remover with active chlorine

Technical information sheet

BAuA-Reg.-Nr.: (D): N-14469



500ml / Item number 101797 / EAN 4016215101797
1l / Item number 101766 / EAN 4016215101766

Powerful mold remover for fast and reliable removal of mold, algae, mildew stains, and bacteria. The effective formula with active chlorine ensures immediate deep action and hygienic cleanliness on mineral surfaces indoors. Ideal for bathrooms, kitchens, basements, and other damp rooms. Works quickly, is easy to use, and helps maintain a clean, well-kept living environment.

- with active chlorine
- Destroys mould, algae, mildew stains and bacteria
- Immediate effect
- Bleaches and disinfects
- Ideal for silicone and tile joints
- Use biocidal products with care. Always read the label and product information before use

Area of application

For removing mould, algae, mildew stains and bacteria from various substrates.

Preparation

Can be used on all mineral substrates such as plaster, concrete, ceramic tiles, bricks and emulsion paint coats.

Processing

Spray the mould-infested surface with mould remover from a distance of approx. 15 - 20 cm. After a contact time of approx. 30 minutes, wipe the treated surface with a damp cloth. Repeat the process in the case of very heavy infestation. To protect the cleaned surfaces from renewed mould infestation in the long term, a follow-up treatment with baufan Protective Impregnation or baufan Protective Paint can be applied after three days. A slight smell of chlorine develops during application, which can last for up to 3 days and can be reduced by sufficient ventilation or airing the treated room. Sensitive and coloured surfaces such as wallpaper, carpets, textiles, clothing, wood and metals can be discoloured on the surface. Discolouration may also occur on damaged tiles. Protect surfaces not to be treated from spray mist and splashes. Accidental splashes should be removed immediately with water.

Consumption

approx. 50 - 100 ml/m²

Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least until: see batch label.

Notes

Processing temperature: at least + 5 °C for material and circulating air Keep out of the reach of children. Do not inhale aerosol. Use only outdoors or in well-ventilated areas. Wear protective gloves/eye protection. IF IN EYES: Rinse with water for several minutes. Remove contact lenses if possible. Continue rinsing. If eye irritation persists: Seek medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. Avoid release into the environment. Caution! Do not use together with other products, as hazardous gases (chlorine) may be released. Contains: Sodium hypochlorite solution <5 % active chlorine Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.