



Transparent, odourless protective impregnation for areas at risk of mould. Forms a long-term film protection against renewed mould infestation and reduces moisture absorption. Ideal for living rooms, bedrooms and children's rooms as well as kitchens, bathrooms, cellars and damp rooms. For wallpaper, plaster, masonry and paintwork.

- With long-term film protection against mould infestation
- Odourless
- Suitable for living rooms, bedrooms and children's rooms
- For wallpapered and painted walls, plaster and masonry
- Transparent

Area of application

For living rooms, bedrooms, children's rooms, kitchens, bathrooms, cellars and damp rooms. Ideal for mould-prone areas on wallpaper, plaster, wood and stone.

Preparation

The surface to be treated must first be cleaned of any mould or spores that may be present. Use baufan mould remover for this purpose. Allow the surface to dry well after cleaning.

Processing

Spray the protective impregnation over the entire surface and at least 1 m beyond the endangered area and allow to dry. The film formed by the protective impregnation protects itself against renewed mould infestation and reduces moisture absorption. Clean tools with water immediately after use.

Consumption

50 - 75 ml/m² 500 ml sufficient for approx. 5 - 7 m²

Storage

Keep container tightly closed and store in a cool but frost-free place. Keep out of the reach of children. Shelf life: 5 years from production date. Production date: see imprint.

Notes

Always check surface compatibility before application. Allow the treated surface to dry thoroughly before further processing. Do not apply below + 5 °C substrate and room temperature. May cause allergic skin reactions. Harmful to aquatic organisms, with long-term effects. If medical advice is required, have packaging or labelling ready. Keep out of the reach of children. Avoid inhalation of vapour/aerosol. Wear protective gloves/eye protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Avoid release into the environment. Only dispose of empty containers for recycling. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of liquid residues according to waste code no. 08 01 12.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.