Protective Paint

Technical information sheet

250ml / Item number 020289 / EAN 4016215020289



Highly opaque, white protective paint with integrated long-term film protection for reliable prevention of mould and fungal infestation indoors. Ideal for wall and ceiling surfaces in kitchens, bathrooms and other damp rooms. The paint is easy to apply with the integrated application brush and impresses with its high coverage, scrub-resistant surface and even, matt finish - for permanently clean, hygienic and well-maintained rooms.

- Tube with application brush
- with film preservation for long-term protection of the paint film against mould infestation
- High opacity
- abrasion-resistant
- for indoors

Area of application

White special paint with film protection against mould. Highly opaque, clean directly from the tube with a brush on interior walls and ceilings.

Preparation

For substrates such as concrete, masonry, levelling compounds, cement, gypsum and lime plaster, plasterboard and other drywall, firmly adhering emulsion paint coats as well as woodchip, glass fabric and other paintable wallpaper and wall coverings. Ceiling panels made of polystyrene and similar surfaces. The substrate must be dry, clean, sound and free of dust and grease. Remove loose material, old wallpaper and poorly adhering paints from the substrate. Prime highly absorbent, sanding and chalking substrates with baufan Deep Primer LF. Repair cracks, holes and unevenness with a suitable baufan levelling compound. Surfaces already infested with mould must be cleaned with baufan Mould Remover before applying the first coat.

Processing

Remove existing mould infestation with mould remover. Shake the tube well before use and apply the protective colour evenly to the area to be repaired. If a second coat is required, the process can be repeated after the first coat has dried. Clean the brush thoroughly with water after use. Drying time: approx. 6 - 8 hours under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); in unfavourable conditions, the drying time will be longer.

Consumption

Smooth surfaces/fine plaster grain → from 150 ml/m² Determine exact consumption quantity by test coating on the object.

Storage

Keep container tightly closed and store in a cool but frost-free place. If unopened and stored properly, shelf life is at least 36 months from date of manufacture (see batch label).

Notes

Processing temperature: Not below +5 °C for material, circulating air and substrate Do not cover surfaces to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Do not inhale spray mist. Avoid eating, drinking and smoking while using the paint. For safety-relevant data, please refer to the safety data sheet. Current safety data sheets are available on our website www.baufan.de or at info@baufan.de.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.