

Multi-Purpose Filler

Technical information sheet

500g / Item no.101056 / EAN 4016215101056

1kg / Item no.101070 / EAN 4016215101070



A versatile filler for repairing and smoothing mineral substrates (such as plaster, concrete and masonry), as well as wood, chipboard, painted surfaces and similar substrates in interior applications. This smooth filler is easy to apply and, once thoroughly dry, is very easy to sand.

- Fine levelling compound for mineral substrates, wood and painted surfaces
- solvent-free
- easy to apply and smooth
- Quick drying
- Easy to sand
- paintable
- for indoors

Area of application

A fine-grain filler for levelling out minor imperfections on plaster, concrete, plasterboard, wood and painted surfaces.

Preparation

The substrate must be clean, dry, sound and uniformly absorbent, and free from dust and grease. Remove any loose material, old wallpaper and poorly adhering paint from the substrate. Prime highly absorbent, sandy or chalky substrates with baufan Tiefgrund LF.

Processing

Stir before use and apply with a trowel to a layer thickness of 3 mm. If a thicker application is required, a further coat can be applied with a trowel once the first coat has dried thoroughly. Clean tools with water immediately after use. Once fully dry, the filled surface can be sanded and painted over very easily.

Drying time:

approx. 1-2 hours per mm of layer thickness under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); under unfavourable conditions, the drying time will be correspondingly longer.

Tinting:

With universal tinting concentrates.

Storage

Store the container tightly sealed in a cool place, but away from frost.

Notes

Application temperature:

+5 °C to +30 °C for the product, ambient air and substrate

The filler is ready to use and must not be diluted with water.

Keep out of the reach of children. Do not allow the product to enter the sewerage system, watercourses or the ground.

Please refer to the safety data sheet for safety-related information. Up-to-date safety data sheets are available on our

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.

website at www.baufan.de.

Disposal:

Only send completely empty containers for recycling. Dried-out material residues may be disposed of with household waste or as construction site waste. Dispose of uncured residues in accordance with waste code 08 04 10.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.