

# Facade and Damp Space Filler

## Technical information sheet

400g / Item no.020333 / EAN 4016215020333



Ready-to-use, white emulsion levelling compound for interior and exterior wall and ceiling surfaces. Ideal for damp rooms (such as kitchens, bathrooms, garages) and for minor levelling work on facades. Excellent for repairing small cracks and holes and for smoothing uneven surfaces.

- Fibre filler with high strength
- Ideal for damp rooms (such as kitchens, bathrooms and garages) and for small filler jobs on the façade
- easy to smooth
- hardens without cracking
- Weatherproof

### Area of application

Damp room filler for facades, bathrooms and kitchens for smoothing walls and ceilings. Adheres to plaster, concrete and plasterboard, ideal for mineral surfaces.

### Preparation

The substrate must be dry, sound and free of separating agents (dust, formwork oil, etc.). Remove poorly adhering coats of paint and loose plaster. Pre-fill deep holes in exterior areas with baufan exterior filler. Highly absorbent, sanding and chalking substrates must be primed with baufan Deep Primer LF.

### Processing

Knead the tube well before use. Apply baufan Facade and Damp Room Filler with a smoothing trowel to a maximum layer thickness of 5 mm. Uneven areas can be smoothed or felted with a damp cloth. Do not apply subsequent coats of paint or bonding until the levelled surface is completely dry. Clean tools with water immediately after use. Drying time: approx. 4 - 7 hours depending on application thickness, substrate and temperature

### Consumption

per mm application thickness --> approx. 1.7 kg/m<sup>2</sup>

### Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least 48 months from date of manufacture (see batch label).

### Notes

Processing temperature: at least + 5 °C for material and circulating air The drying time depends on the processing temperature. Relative humidity above 90%, especially in combination with low temperatures, can significantly affect the drying time and quality properties. Product code M-DF02 Waste code no. 080410 (waste adhesives and sealants). Only dispose of empty containers for recycling. Dried material residues can be disposed of according to waste code no. 170904 (mixed construction and demolition waste) or as household waste.

#### Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.