

Tile and joint repair white

Technical information sheet

350g / Item no.004202008 / EAN 4016215101490



High-quality special grout for the quick and clean repair of damaged tile joints. Ideal for kitchens and bathrooms as it is waterproof and durable. Easy to apply, hardens evenly and without cracks and ensures a clean, neat joint appearance. Perfect for visually refreshing and maintaining the value of tiled wall surfaces indoors.

- Special grout for grouting interior wall tiles
- Ideal for the quick repair of damaged tile joints
- waterproof
- for kitchen and bathroom
- hardens without cracking

Area of application

Grout for wall tiles for repairing damaged tile joints. Easy to use, clean application and crack-free hardening. Ideal for bathrooms and WCs.

Preparation

The joints must be dry, clean and free of dust and grease. Remove loose material from the joints. Cover porous and unglazed tiles before grouting.

Processing

Knead the tube well before use. Press bausfan Tile and Joint Repair directly into the joint to be repaired so that the joint is filled without gaps. Carefully remove any excess grout (e.g. with a rubber spatula) before it dries. Wipe the tiles with a damp sponge and rub dry. Once completely dry, the material is waterproof. Drying time: approx. 24 hours/mm application thickness. The drying time may vary depending on climatic conditions and the absorbency of the substrate.

Consumption

Keep the tube tightly closed and store in a cool, frost-free place. Keep out of the reach of children. If unopened and stored properly, shelf life is at least 36 months from date of manufacture (see batch label).

Storage

Keep the tube tightly closed and store in a cool, frost-free place. Keep out of the reach of children. If unopened and stored properly, shelf life is at least 36 months from date of manufacture (see batch label).

Notes

Processing temperature: Do not store below +5 °C for material, circulating air and substrate. Keep out of reach of children. Ensure adequate ventilation during processing and drying. Avoid eating, drinking and smoking while using the paint. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.