Cellar colour

Technical information sheet

5L / Item number 116602008 / EAN 4016215103197



White, silicate-based mineral interior paint in accordance with DIN 18363, specifically designed for use in basements. This preservative-free paint, based on potassium water glass, is suitable for creating a pleasant indoor climate. baufan Cellar Paint is virtually odourless and, with Class 2 opacity, offers very good coverage.

- Highly permeable
- for mineral substrates
- ideal for basement and garage walls

Area of application

White silicate interior paint for use in basements in accordance with DIN 18363. Low odour, preservative-free, high opacity, promotes a healthy indoor climate and provides excellent coverage.

Preparation

For all mineral substrates such as plaster, concrete or masonry as well as for existing, load-bearing silicate coatings. The substrate must be clean, dry, sound and free from dust, grease or loose particles. Highly absorbent, sanding or chalking surfaces must be primed in advance with baufan Silicate Fixative. Repair cracks, holes and unevenness with a suitable baufan levelling compound.

Processing

Stir well before use and apply with a roller, brush, paintbrush, flat brush or suitable spraying equipment. One to two coats are recommended, depending on the absorbency and condition of the substrate. The primer can be diluted with max. 10 % baufan Silicate Fixative. After the first coat of paint has dried through, apply the top coat undiluted. Depending on the absorbency of the substrate and the room climate, the drying time is approx. 5 hours; in unfavourable conditions (e.g. low temperature or high humidity), the drying time may be longer.

Consumption

approx. 125 ml/m² per coat. Determine the exact amount used by trial application on the object.

Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least until: see batch label.

Notes

Observe the technical data sheet. Processing temperature for material, circulating air and substrate not below +5 °C. Clean tools with water immediately after use. Ensure thorough ventilation during application and drying. Avoid eating, drinking and smoking while using the paint. Keep out of reach of children. Avoid contact with the eyes and skin due to the high pH value. We recommend wearing gloves and safety goggles (no glass). In case of skin contact, rinse with plenty of water. In case of eye contact, rinse immediately with plenty of water and seek medical advice if necessary. Use combination filter A2/P2 for spraying work. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling. Store tightly closed and cool, but frost-free. Batch no. see imprint.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.