

Glued ceiling and wall paint

Technical data sheet

2kg / Item no.099797 / EAN 4016215099797

Glued ceiling and wall paint made from natural raw materials for high-quality interior coatings. Breathable and water vapour permeable, ideal for mineral substrates and wallpaper. Highly opaque, naturally white and preservative-free. For clean, wipe-resistant and durable interior surfaces.

Area of application

Distemper for interior wall and ceiling surfaces.

Preparation

For all mineral substrates (such as concrete, masonry, levelling compounds, cement, gypsum and lime plaster), plasterboard and other drywall, firmly adhering emulsion paint coats as well as woodchip and wallpaper. The substrate must be dry, clean, stable, evenly absorbent and free of dust and grease. Remove loose material, old wallpaper and old distemper, poorly adhering coats of paint from the substrate. Prime highly absorbent, sanding and chalking substrates with baufan Deep Primer LF. Repair cracks, holes and unevenness with a suitable baufan levelling compound.

Processing

Sprinkle the contents of the pack into 2 litres of clean, cold water while stirring vigorously and continue stirring for a short time. Stir well again after 2 hours. For optimum results, we recommend mixing the paint the day before and leaving it to soak overnight. The paint can be applied with a roller, brush, brush or flat brush. If the colour of the substrate varies greatly, it is recommended to apply a second coat after the first coat has dried completely. Clean tools with water immediately after use. Drying time: approx. 5 hours under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); longer drying time under unfavourable conditions. Tinting: With universal tinting concentrates or solid colour and tinting paint.

Consumption

Smooth surfaces/fine plaster grain → 2 kg for approx. 15 m² Determine the exact consumption quantity by applying a test coat to the object.

Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least 60 months from date of manufacture (see batch label)

Notes

Processing temperature: +5 °C to +30 °C for material, circulating air and substrate As baufan Glued Ceiling and Wall Paint does not contain any preservatives, the mixed product must be processed within 2 days. To increase the wipe resistance, baufan Latex Binder can be added to the prepared paint - the amount of water must be reduced according to the amount of binder added. Cover surfaces that are not to be painted. Keep out of the reach of children. Ensure adequate ventilation during application and drying. Avoid eating, drinking and smoking while using the paint. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling. For safety-relevant data, please refer to the safety data sheet. Current safety data sheets are available on our website www.baufan.de or at info@baufan.de.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.