

Aqua-Deck White Stain Blocker

Technical information sheet

750ml / Item no.020173 / EAN 4016215020173

2,5l / Item no.020180 / EAN 4016215020180

10l / Item no.020203 / EAN 4016215020203



White, water-based renovation and insulating paint with excellent hiding power for interior use. Prevents the penetration of nicotine, water marks, soot and grease stains, colouring substances from plasterboard and wood panels and similar contaminants on the substrate. Is ideal as a matt top coat, but can also be reworked in the usual way with wallpaper, emulsion paints and plasters.

- Solvent-free renovation paint with high opacity
- Prevents the penetration of nicotine, soot, grease and water stains
- Isolates colouring substances from plasterboard, OSB and wood building boards
- 2 in 1 - insulating paint and top coat
- Contrast ratio class 1 with a coverage of 6 m²/l
- Wet abrasion resistance class 2 according to DIN EN 13300
- Gloss level dull matt
- airless sprayable
- for indoors

Area of application

White insulating paint for interiors: covers nicotine, soot, grease and water stains - ideal for quick renovations in living spaces and hotels.

Preparation

For substrates such as concrete, cement and lime-cement plaster, masonry, gypsum substrates, fibre cement boards, also for adhesive dispersion plasters and wallpapers. Suitable as a top coat or can be recoated with wallpaper, emulsion paints and plasters. All substrates must be clean, dry, sound, absorbent and free of release agents. Use **baufan Deep Penetrating Primer LF** to increase the strength. Substrates that cannot be consolidated or do not adhere sufficiently must be completely removed. If in doubt, apply a test coat. Clean extremely contaminated substrates with grease-dissolving household cleaning agents. Pre-treat heavy nicotine, soot or grease stains and deposits mechanically (scrape off, sand down).

Processing

Stir well before use and apply with a roller, brush, paintbrush, flat brush or suitable spraying equipment. Apply the product undiluted. When coating larger areas, work wet on wet to avoid build-up. Clean tools with water immediately after use. Do not mix with other materials, including emulsion and solid colours. The insulating effect depends on the respective object situation. It is recommended to create test areas on site before application. Drying time: approx. 12 hours under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); longer drying time in unfavourable conditions. Tinting: Tinting is possible with decoMIX tinting concentrates (LW oxide types only) up to max. 0.2% without impairing the insulating effect. Notes on airless spray application Spray angle: 50° Nozzle: 0.023 - 0.027 Spray pressure: 120 - 180 bar

Consumption

Smooth surfaces/fine plaster grain → from 150 ml/m² Determine exact consumption quantity by test coating on the object.

Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least until: see batch label.

Notes

Processing temperature: +5 °C to +30 °C for material, circulating air and substrate Do not cover surfaces to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Do not inhale spray mist. Avoid eating, drinking and smoking while using the paint. Wear safety goggles. In case of contact with eyes or skin, rinse

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.

immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling. caution! Hazardous respirable droplets may be produced when spraying. Do not inhale aerosol or mist. Use combination filter A2/P2 when spraying.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.