Spray Anti-Taches

Technical information sheet

400ml / Item number 101995 / EAN 4016215101995



Quickly and permanently isolates stains and water-soluble soiling - such as water, soot, fire, grease and tar stains, nicotine, felt-tip and photocopying pens, etc. - simply by spraying on. Prevents the stains from penetrating later when wallpapering or painting with emulsion paints. Not suitable for permanent markers containing solvents.

- Isolates grease, soot, water stains etc.
- Quick drying
- inside and outside

Area of application

Insulating spray against water, soot, grease, tar and nicotine stains. Prevents penetration before wallpapering or painting with emulsion paint.

Preparation

The substrate must be solvent-resistant, stable and dry.

Processing

Shake can vigorously before use. To remove the cap, insert an 8 mm wide screwdriver into the bulge on the side of the cap and twist. Then spray briefly. Briefly spray the spots to be insulated from a distance of approx. 20 cm so that a closed surface without imperfections is created. In the case of rough surfaces or very heavy soiling, repeat the process after approx. 10 minutes if necessary. Drying time: The treated surfaces can be wallpapered or painted over with emulsion paint after a drying time of approx. 10 minutes.

Storage

Keep container closed and store in a cool but frost-free place. Keep out of the reach of children.

Notes

Do not use below +5 °C object and room temperature. For safety-relevant data, please refer to the safety data sheet. Current safety data sheets are available on our website www.baufan.de or at info@baufan.de. Disposal: Only dispose of empty containers for recycling. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of uncured residues according to EWC waste code no. 16 05 04.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.