Concrete Contact 710

Technical information sheet

/ Item number 069404208 / EAN 4016215105009



Water-based special primer for improving the adhesion of gypsum-, cement- and lime-based fillers and plasters to smooth, non-absorbent or slightly absorbent mineral surfaces (particularly concrete). Particularly suitable for smooth in-situ concrete or solid concrete slabs made from precast elements, as well as for smoothed precast concrete surfaces and rigid polystyrene foam boards. The product's slightly reddish colour makes it easy to identify areas that have already been treated.

- high alkali resistance
- tinged with red
- free from solvents and plasticisers
- non-slip surface
- for indoors

Area of application

Water-based bonding primer for smooth mineral surfaces (particularly concrete).

Preparation

The substrate must be sound, dry and free from loose particles and release agents (formwork oil, curing agents, etc.). Moisture and moisture wicking up from the substrate must be prevented. Cover any areas not to be treated, as splashes are difficult to remove later.

Processing

Stir profimur Betonkontakt before use and apply with a roller, brush, paintbrush or a suitable spraying device (screw pump). Only when applying by machine should you, if necessary, adjust the consistency to a sprayable state by adding a small amount of water. When applying by hand, apply in criss-cross strokes, wet-on-wet. Do not carry out any subsequent work until the product has dried through completely. Drying time: at least 24 hours – depending on temperature and humidity. At low temperatures and high humidity, drying times will be correspondingly longer. Before plastering, check the degree of dryness by carrying out a wipe test.

Consumption

Approx. 250 g/m² per coat – depending on the substrate. Determine the exact application rate by carrying out a test application on the surface.

Storage

Keep container tightly closed, childproof and store in a cool but frost-free place.

Notes

Do not apply when the object or ambient temperature is below +5 °C. In case of contact with the eyes, rinse immediately with water. When applying by spraying, do not inhale the spray mist. Clean tools with water immediately after use.

Please refer to the safety data sheet for safety-related information. Up-to-date safety data sheets are available on our website at www.baufan.de or at info@baufan.de.

Only send completely empty containers for recycling. Dried-out material residues may be disposed of as household waste or as construction site waste. Dispose of liquid residues in accordance with waste code EWC 08 01 12. Do not allow the product to enter the drains, watercourses or the ground.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.