

Lime paint 721

Technical information sheet

/ Item no.068503208 / EAN 4016215105276



A washable interior paint based on white hydrated lime, suitable for living and sleeping areas, as well as kitchens, bathrooms and utility rooms. It helps to regulate humidity and balance the indoor climate.

- ideal for all living and utility spaces
- Highly water vapour permeable
- free from preservatives, solvents and plasticisers
- highly breathable
- for indoors
- Resistance to wet abrasion: Class R 3
- Contrast ratio H₁₀ Class 2 with a coverage of 6 m²/l

Area of application

Ready-to-use, white lime paint for the entire living and sleeping areas, as well as the kitchen, bathroom and utility rooms.

Preparation

Suitable for use on mineral substrates (such as lime and cement plaster, etc.) as well as on painted surfaces. The substrate must be firm, dry, sound, alkali-resistant, and free from dust and grease. Prime highly absorbent, sandy and chalky substrates, as well as sanded surfaces, with a silicate fixative.

Processing

Stir profimur lime paint thoroughly before use and apply with a paintbrush, roller or a suitable spray gun. Apply undiluted for a single coat. For two coats, the first coat may be diluted with up to 5 per cent water. Drying time: at least 8 hours (depending on ambient conditions).

Airless spraying recommendation:

Before application, dilute with up to 10 per cent water and strain without pressure (nozzle size 0.5 mm).

Nozzle: 519 – 527; spray pressure: 120 – 170 bar

Consumption

Approx. 150 ml/m² per coat – depending on the substrate and application method. Determine the exact consumption by carrying out a test application on the surface.

Storage

Keep container tightly closed, childproof and store in a cool but frost-free place.

Notes

Protect surfaces not to be painted (such as glass, wood, etc.) from splashes and spray mist. Do not apply when the surface and ambient temperatures are below +5 °C. Clean tools with water immediately after use.

Only send completely empty containers for recycling. Dried-out material residues may be disposed of as household waste or as construction site waste. Dispose of liquid residues in accordance with EWC code 08 01 12. Do not allow the product to enter the sewerage system, watercourses or the ground.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.