

Lightweight Filler 910

Technical information sheet

/ Item no.034601208 / EAN 4016215105313



Ultra-lightweight, white filler for filling joints, cracks and holes in walls and ceilings, as well as for the joints between door and window frames and skirting boards. Ideal for filling interior insulation boards, stucco mouldings and decorative elements made of rigid foam and polystyrene. Remains slightly flexible even after curing and adapts to the natural movements of the substrate.

- for perfect butt joints
- white
- flexible
- can be sanded and painted over
- Can be used indoors and also outdoors with a weather-resistant top coat

Area of application

A flexible, lightweight filler for filling joints, cracks and holes in walls and ceilings, as well as for the joints between door and window frames and skirting boards.

Preparation

Suitable for all mineral substrates (such as concrete, plaster and masonry) as well as for wood, polystyrene, emulsion paint finishes, varnished surfaces, synthetic resin plasters and similar substrates. The substrate must be clean, dry, sound, and free from dust and grease. Pre-treat highly absorbent, sandy and efflorescent substrates with profimur Deep Primer LF.

Processing

Before use, cut off at least 1 cm of the nozzle. Apply the profimur Light Filler to a maximum layer thickness of 15 mm and smooth it out. Once thoroughly dry (approx. 8 hours, depending on the application thickness and environmental conditions), the profimur Light Filler can be sanded very easily. When used outdoors, apply a weather-resistant coat shortly after it has thoroughly dried.

Storage

Keep container tightly closed, childproof and store in a cool but frost-free place.

Notes

Do not use at temperatures below +5 °C. Clean tools with water after use.

Please refer to the safety data sheet for safety-related information. You can obtain the latest safety data sheets from our website www.baufan.de or at info@baufan.de.

Only send completely empty containers for recycling. Dried-out material residues can be disposed of as household waste or as construction site waste. Dispose of uncured residues in accordance with EWC code 08 04 10. Do not allow the product to enter the drainage system, watercourses or the ground.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.