

Super-Adhesive Filler 945

Technical information sheet

/ Item no.003904208 / EAN 4016215105016
/ Item no.003908208 / EAN 4016215105030



This synthetic resin-modified, fibre-reinforced filler offers outstanding adhesion and stability. It is ideal for full-surface skimming and for jointing plasterboard and gypsum fibreboards – even without reinforcement tape. It can be levelled down to zero, enabling the creation of seamless, smooth surfaces in drywall construction and painting applications.

- Painting and plasterboard filling trowel for interior use
- Ideal for full-surface skimming and for jointing stress-free plasterboard and gypsum fibreboard panels, even without reinforcement tape ‡ For all plasterboard systems in accordance with EN 13963
- synthetic resin-coated and fibre-reinforced
- Extendable to zero for seamless surfaces
- Fire performance: A1 (EN 13501-1)
- CE-compliant in accordance with DIN EN 13963-4B and DIN EN 13279-1 (gypsum surface filler C7/20/2)

Area of application

High-adhesion gypsum filler for living areas, hallways and offices: smooths walls and ceilings, fills joints, cracks and holes in plasterboard.

Status: 16.09.2026

Page 1/1

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Phone +49 (0)341 44655-0 ■ E-mail info@baufan.de ■ Internet www.baufan.com

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.