



Farb-Ex FS plus

Technical information sheet

400ml / Item no.110102000 / EAN 4007954101308



Highly effective spray paint remover for the effortless removal of paint, varnish, resin, oil and grease stains. Also adheres to vertical surfaces, has very high dissolving power and enables precise dosing. Suitable for numerous solvent-resistant substrates.

- Very high dissolving power
- Also adheres to vertical surfaces
- CHC- and NMP-free
- Precisely dosable spray

Area of application

Farb-Ex FS plus Colour Remover Spray removes old layers of paint and varnish from wood, stone, metal and selected plastics.

Processing

Shake can vigorously for 1 - 2 minutes before use. Spray the surface to be treated from a distance of approx. 20 cm. After a reaction time of approx. 20 minutes, remove the layers of paint using a metal spatula. If necessary, repeat the process for multiple coats of paint. Then rinse the surface thoroughly with water. After use, turn the spray can upside down and spray the nozzle empty to prevent the material from drying in the nozzle head.

Storage

Keep container tightly closed and store in a cool place. Keep out of the reach of children.

Notes

Formation of explosive/highly flammable mixtures possible with insufficient ventilation and/or through use. Ensure adequate ventilation. Test the resistance of the substrate in an inconspicuous place before use. As some plastics and non-solvent-resistant materials can be attacked, it is advisable to cover them. Cannot be used on glass and plastic with the exception of POM, PVC, PC and PP-EPDM. Do not use plastic tools and dispose of the stripped residues at a hazardous waste collection point. Dispose of product residues as hazardous waste. Only dispose of empty cans for recycling.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.