# Linseed Oil Putty

Technical information sheet

500g / Item number 520810 / EAN 4016818390666
1kg / Item number 520812 / EAN 4016818390673




High-quality window putty for durable glazing and repairs. Easy to apply and provides a weather-resistant seal for glass panes in wooden and metal frames.

- in accordance with DIN 18545 A
- Proven quality
- plastoelastic
- paintable
- Colour beige

## Area of application

Glazier’s putty for single glazing and repair glazing on wooden windows with an exposed sealant chamfer.

## Preparation

The window frame must be clean, dry and free of grease. The rebates must be primed (with acrylic paint or an alkyd resin primer). However, to ensure optimum adhesion of the glazing putty, the primer must not be applied so thickly that it blocks the pores of the wood.

## Processing

Once the putty has been kneaded thoroughly, press it firmly into the rebate and smooth the surface with a putty knife. During the drying period, it is essential to ensure that any condensation that may form does not penetrate the putty bed. As the putty requires oxygen to set, double-glazed windows must not be assembled immediately after glazing. Once the putty has hardened – after 4–8 weeks at the latest –
it must be coated with a weather-resistant, elastic paint. Painting over it too soon can lead to wrinkling. In the case of acrylic paints, test applications should always be carried out first.
The provisions of the BFS guideline, DIN 18361 and DIN 18545 must be strictly observed.

## Consumption

500 g for approx. 50 - 60 cm

## Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, it will keep for at least 24 months from the date of manufacture (see label).

## Notes

Application temperature:
at least +8 °C for the material and ambient air.

Before use, refer to the safety information in the safety data sheet. Up-to-date safety data sheets are available on our website at www.baufan.com.

Keep out of the reach of children. Do not allow the product to enter the sewerage system, watercourses or the ground. Only send completely empty containers for recycling.



Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

**Note:**
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.