

1,5kg / Item no.003315000 / EAN 4007954033159

5kg / Item no.003313000 / EAN 4007954033036



Pure natural plaster (alabaster) for interior building and hobby work. Fast hardening and easy to work with. Ideal for filling holes and cracks, plastering in dowels and fixing interior plaster boxes and cable slots. Suitable for assembly, renovation and handicraft work.

- Fast-hardening natural gypsum
- Electrician's plaster for fixing interior plaster boxes and filling cable slots
- for indoors
- CE-compliant in accordance with DIN EN 13279-1 (gypsum binder for direct use or further processing A1)

Area of application

Electrician's plaster for fixing interior plaster boxes, filling holes and cracks as well as for filling cable slots and plastering.

Preparation

The substrate must be dry, stable, solid and free of separating agents (e.g. dust and grease). Pre-treat highly absorbent, sanding and chalking substrates with Deep Primer LF.

Processing

The mixed plaster compound remains workable for approx. 10 minutes. Do not load until completely dry (after approx. 24 hours depending on the substrate condition and ambient temperature). Once completely dry, the levelled surfaces can be sanded or painted with emulsion, latex, oil or varnish paints if required. Do not use lime or water-based paints. Sprinkle 2 parts of modelling plaster into 1 part of cold, clean water and stir vigorously.

Storage

Store tightly closed in a cool, dry place. Keep out of the reach of children.

Notes

Clean tools with water immediately after use. Only dispose of empty containers for recycling. Dried material residues can be disposed of with household waste or as construction site waste. EWC waste code no. 17 08 02.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.