

Painter Universal Fabric Large roll 25 m²

Technical information sheet

1 Rolle / Item no.009602000 / EAN 4007954096024



Universal painter's fleece made of glass fibre for quick and clean renovation of wall and ceiling surfaces. Bridges cracks, levels out unevenness and creates a stable substrate for paints or coatings. Easy to apply, tear-resistant and suitable for indoor and outdoor use.

- produces smooth surfaces without subsequent levelling
- Optimum processing with decofill ready-mixed filler
- Glass fibre fleece

Area of application

Restoration solution for lightly textured substrates such as glass fibre wallpaper and plastic plaster - ideal for repairing cracks on walls and ceilings.

Processing

Apply the levelling compound evenly to the substrate using a notched trowel. If the substrate is smooth, the fleece can also be bonded directly to the substrate with paste or dispersion adhesive. Lay the painter's fleece vertically into the fresh levelling compound or the fresh adhesive bed without creases or bubbles and press flat with a smoothing trowel up to 5 cm from the edge. Place the second sheet overlapping the first sheet by approx. 5 cm. Use the cutter knife to cut through both sheets at the same time in the centre of the overlapping area (double seam cut). Remove the upper and lower cut strips and press the seam area with the smoothing trowel. If the substrate is uneven, the surface can be smoothed with a sponge board and a little water. Once completely dry, prime the renovated surface with a solvent-free primer, e.g. decotric Tiefengrund LF.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.