

Solupast D Solvent

Technical information sheet

1l / Item no.120202000 / EAN 4007954 20232 6

6l / Item no.120204000 / EAN 4007954202340



Quickly and reliably removes residues from floor coverings and dispersion or synthetic resin adhesives. Removes dried stains from emulsion paints, synthetic resin and acrylic lacquers. Cleans dirty tools and hard natural hair brushes.

- Gel formula
- Highly effective
- Contains aromatic-free solvent

Area of application

Solupast D removes floor covering residues, adhesive residues and paint stains quickly and safely - ideal for tools, brushes and renovations.

Processing

Floor covering and adhesive residues: Apply Solupast D generously with a solvent-resistant brush or roller and allow to react for 15 - 60 minutes, depending on the adhesive. Remove the dissolved adhesive layer with a spatula. Repeat the process if necessary. Wash the surface thoroughly with water and detergent if necessary and allow to dry completely. Dried paint and varnish stains: Allow Solupast D to work for approx. 10 - 30 minutes and rub the stain with a cloth to dissolve it. Rinse thoroughly with water. Cleaning: Soak hard natural hair brushes in Solupast D in a glass or metal container and rinse after sufficient exposure time. Place smaller metal parts in Solupast D, coat larger metal parts and also rinse with water.

Storage

Keep container tightly closed, childproof and store in a cool but frost-free place.

Notes

Solupast D is evaporation-delayed, therefore long exposure times are possible without repeated application. Solupast D is a thixotropic gel and can also be applied to vertical surfaces. Non-solvent-resistant plastics and mastic asphalt may be attacked. Test surface compatibility in an inconspicuous area before application. Do not use Solupast D on absorbent substrates (e.g. cement screed). Treat larger areas in sections of max. 0.5 m², ensuring good air circulation. Before subsequent work or laying new floor coverings, allow the substrate to dry completely and ventilate the room well. Only dispose of empty containers for recycling. Dried material residues can be disposed of with household waste or as construction site waste. EWC waste code no. 08 04 12.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.