



Ready-to-use, solvent-free dispersion adhesive. Ideal for fast and secure bonding of wood, PVC cable ducts, decorative mouldings, polystyrene decorative and insulating panels, ceramic wall tiles, PVC skirting boards and similar materials indoors.

- Universally applicable
- for wood, PVC cable ducts, decorative mouldings, decorative and insulating panels made of polystyrene, ceramic wall tiles, PVC skirting boards, etc.
- High strength
- solvent-free
- for indoors

Area of application

Assembly adhesive for skirting boards, wooden panels, decorative and insulating boards, decorative profiles, tiles and mosaics. For many interior applications.

Preparation

The substrate must be sufficiently absorbent, dry, stable and free of separating agents (grease, dust, etc.). Sanding and chalking substrates must be pre-treated with bausfan Tiefgrund LF. If the material to be bonded cannot absorb moisture, the substrate must be absorbent.

Processing

Knead the tube well before use. Apply bausfan assembly adhesive in dots or strips to the parts to be assembled and press down firmly. Heavy parts must be fixed in place until the adhesive has hardened. Remove adhesive residues immediately with clear water. Drying time: approx. 24 hours under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); under unfavourable conditions, the drying time will be longer.

Consumption

depending on substrate and application thickness ► approx. 300 - 500 g/m² Tube content is sufficient for approx. 12-20 running metres.

Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least 48 months from date of manufacture (see batch label).

Notes

Processing temperature: +5 °C to +30 °C for material, ambient air and substrate Keep out of reach of children. Ensure adequate ventilation during processing and drying. Avoid eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.