

Wallpaper Adhesive Power

Technical information sheet

200g / Item no.102558 / EAN 4016215102558



High-quality methylcellulose paste in top quality with particularly high wet strength for professional wallpapering work. Ideal for paintable wallpapers and versatile use with woodchip, textured and non-woven wallpapers, non-woven woodchip, vinyl and embossed wallpapers as well as roll wallpaper. Easy to mix and apply evenly, ensures reliable adhesion and clean, long-lasting results.

- for textured, embossed, non-woven and vinyl wallpapers, woodchip and non-woven woodchip wallpaper
- made of high-quality methyl cellulose with synthetic resin
- High moisture resistance when painting over
- Strong initial adhesion and adhesive strength
- Very good adjustability of the wallpaper panels
- Ready to use in 15 minutes
- machinable
- dries transparent
- free from preservatives

Area of application

Wallpaper paste for paper, vinyl, non-woven and woodchip wallpapers. Very high wet strength, ideal for textured wallpaper and paintable woodchip wallpaper.

Preparation

The substrate must be dry, stable and free of dust and grease. Remove old poorly adhering wallpaper and distemper with baufan wallpaper stripper. Repair cracks and holes with baufan interior filler or decomur super adhesive filler. Pre-treat highly absorbent, sanding and chalking substrates with baufan Deep Penetrating Primer LF or pre-paste (1:40 ratio). To make it easier to change the wallpaper later, it is recommended to prime the substrate with baufan Wallpaper Changing Primer, especially for washable wallpapers.

Processing

Mixing ratio: Pre-pasting: Mix 1:40 = 8.0 litres of water = 60-80 m² Rough wallpaper: Mix 1:20 = 4.0 litres of water = 20-25 m² Textured, non-woven, vinyl, embossed and heavy wallpaper: Mix 1:20 = 4.0 litres of water = 22-25 m² Pour paste into clean, cold water while stirring vigorously and stir again after 2 - 3 minutes. Stir again vigorously after approx. 15 minutes. Apply the paste to the wallpaper with a brush or wallpapering machine, lay the wallpaper strips together and apply after sufficient soaking time. Remove any remaining paste immediately with a damp cloth. Do not paint over the glued wallpaper until the paste is completely dry. Follow the wallpaper manufacturer's instructions for use. To increase the adhesive strength of heavy special wallpapers and glass fibre, a can of baufan Wallcovering Adhesive 750 g per packet of baufan Kraft-Kleister 200 g can be added. baufan Kraft-Kleister is lime and cement resistant. Clean tools with water after use.

Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least until: see batch label.

Notes

Processing temperature: +5 °C to +30 °C for material, ambient air and substrate Keep out of reach of children. Ensure adequate ventilation during application and drying. Avoid eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.