# Roller Adhesive for non-woven wallpapers

Technical information sheet

5kg / Item number 103227 / EAN 4016215103227




Ready-to-use wallpaper paste that can be applied straight from the bucket - no mixing required. Ideal for efficient roller wallpapering and for classic application with a paste brush. Spreads evenly, offers reliable adhesion and ensures a clean, bubble-free application. Perfect for quick, convenient and professional interior wallpapering work.

- ready for use
- for smooth and embossed non-woven wallpapers and non-woven raw fibre
- with the roll directly onto the wall
- Does not splash or drip
- High initial adhesion and bonding strength
- Easily correctable
- dries out transparently

## Area of application

Non-woven wallpaper paste for non-woven wallpapers and dimensionally stable wall coverings. Ideal for clean wall adhesion, easy to apply and securely adhesive. For living spaces.

## Preparation

The substrate must be dry, clean, sound, level, evenly absorbent and free of dust and grease. Remove old wallpaper and poorly adhering paint. Cracks. Repair holes and unevenness with baufan interior filler. Prime highly absorbent, sanding and chalking substrates with baufan Deep Primer LF. If translucent non-woven wallpapers are to be applied to substrates of uneven colour, we recommend priming with baufan Wallpaper Primer White.

## Processing

Wall pasting technique (application to the substrate): As non-woven wallpapers do not require a soaking time, they can be applied quickly and easily using the wall pasting technique. To do this, apply the paste evenly to the substrate on a short-pile roller in the width of 1 - 2 wallpaper panels. Place the wallpaper sheet in the fresh paste bed and press down evenly and bubble-free. The "open time" of the paste is approx. 10 to 15 minutes and refers to approx. +20°C object and room temperature, on moderately absorbent substrates at 50 to 70% relative humidity. Application to the wallpaper: Spread the wallpaper evenly with a paste brush and apply butt joints according to the manufacturer's instructions. Immediately remove any excess adhesive from the joints with a clean, damp cloth. Paintable wall coverings may only be painted over after the adhesive has completely dried. Clean tools with water after use. The wallpaper manufacturer's instructions must be observed. Drying time: approx. 24 hours under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); longer drying time under unfavourable conditions.

## Consumption

approx. 200g/m² content is sufficient for approx. 5 Euro rolls = approx. 25 m² (Euro roll = approx. 10.05 m x 0.53 m)

## Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least 24 months from date of manufacture (see batch label).

## Notes

Processing temperature. +5 °C to +30 °C for material, ambient air and substrate Keep out of reach of children. Ensure adequate ventilation during processing and drying. Avoid eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty



Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

**Note:**
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.

containers for recycling.



Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

**Note:**
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.