Wallpaper Adhesive Special

Technical information sheet

200g / Item no.102350 / EAN 4016215102350

High-quality cellulose derivative with adhesive-reinforcing additives for the reliable adhesion of almost all types of wallpaper. Can also be used on fresh, air-dry plaster and is therefore particularly flexible in application. The paste is easy to mix and easy to work with. For clean, even wallpapering results indoors.

- Reinforced with synthetic resin
- High adhesive strength
- For woodchip and heavy wallpaper
- Ready to use in 30 minutes
- dries transparent
- free from preservatives

Area of application

For pasting all types of wallpaper, including woodchip, embossed, vinyl, photo and special wallpapers.

Preparation

The substrate must be clean, dry, sound, absorbent, smooth and free from release agents. Remove old wallpaper with baufan wallpaper stripper or baufan woodchip stripper. Repair cracks, holes and uneven surfaces with baufan interior filler. Prime sanding and chalking substrates with baufan Deep Primer LF. Pre-paste highly absorbent substrates (1:40 ratio) or pre-treat with baufan Deep Penetrating Primer.

Processing

Mixing ratio: Pre-pasting: Mix 1:40 = 8.0 litres of water = 60-80 m² Rough wallpaper/heavy wallpaper: Mix 1:20 = 4.0 litres of water = 22-26 m² Special wallpapers/unprinted embossed wallpapers: Mix 1:15 = 3.0 litres of water = 10-15 m² Sprinkle the contents of the pack quickly and rapidly into cold water while stirring vigorously and continue stirring for a short time. After approx. 30 minutes, stir the mixture again vigorously. Paste the wallpaper evenly, fold and leave to soak. After the recommended soaking time, apply the wallpaper butt-jointed and press down evenly and bubble-free using a wallpapering brush, roller or spatula. Follow the wallpaper manufacturer's instructions. Clean tools with clear water after use. To increase moisture resistance, for slightly absorbent substrates and for very heavy wallpapers, we recommend adding one tin (750g) of baufan wallcovering adhesive to one pack of special paste, which is stirred into the ready-mixed paste.

Storage

Keep container tightly closed and store in a dry place. If unopened and stored properly, the product will keep for at least 48 months. Date of manufacture: see batch label.

Notes

Processing temperature: +5 °C to +30 °C for material, ambient air and substrate Keep out of reach of children. Ensure adequate ventilation during processing and drying. Avoid eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.