



Wallpaper Seam Adhesive

Technical information sheet

60g / Item no.102657 / EAN 4016215102657



Ready-to-use emulsion adhesive for resealing open wallpaper joints on all surfaces. Also ideal for tricky areas – e.g. around window frames and in radiator recesses.

- High adhesive strength
- for all wallpapers
- solvent-free

Area of application

Ready-to-use emulsion-based adhesive for resealing open wallpaper joints on all surfaces.

Preparation

The substrate must be stable and free of dust.

Processing

Apply baufan wallpaper seam adhesive to the surface or the back of the wallpaper and spread it with a brush or small spatula. Press the wallpaper firmly into place.

Drying time:

Approx. 10–15 minutes under normal conditions (+20 °C, 65% relative humidity, moderately absorbent surface). Under unfavourable conditions, the drying time will be correspondingly longer.

Storage

Store the tube tightly sealed in a cool place, but away from frost.

Notes

Keep out of reach of children. Remove any adhesive residue immediately with a damp cloth. Do not use at temperatures below +5 °C. Clean tools with water immediately after use.

Please refer to the safety data sheet for safety-related information. You can obtain the latest safety data sheets from our website www.baufan.de.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.