



Powerful wallpaper stripper for quick and effortless removal of paper, vinyl and textile wallpapers as well as woodchip. The powerful deep action reliably penetrates the wallpaper layers and removes even stubborn adhesions. Very economical to use and easy to apply with a brush. Ideal for interior renovation work and the perfect preparation for new wall designs.

- Removes wallpaper and woodchip quickly and easily
- Strong depth effect
- Very economical
- Contains biodegradable surfactants

Area of application

For easy removal of paper, vinyl and textile wallpaper as well as woodchip wallpaper.

Preparation

Roughen impermeable wallpaper and painted woodchip in advance with a needle roller or coarse sandpaper.

Processing

For light and medium-weight paper wallpapers, mix 250 ml of wallpaper stripper with approx. 15 litres of water. For heavy wallpapers and woodchip, dilute 250 ml of wallpaper stripper with 8 - 10 l of water. Cover surfaces not to be treated (floors, doors, furniture). Apply the solution generously to the wallpaper using a ceiling brush. Repeat the application if necessary for wallpaper that is difficult to remove. After soaking, the wallpaper can be easily removed. Clean tools with water after use. Residues of the wallpaper stripper can be easily removed with water.

Consumption

1 litre of wallpaper stripper for approx. 150 - 200 m² - depending on dilution

Storage

Keep container tightly closed and store in a cool but frost-free place. Keep out of the reach of children. Only dispose of empty containers for recycling. Dispose of product residues according to EWC waste code no. 07 06 01.

Notes

Keep out of the reach of children. Avoid contact with the eyes! Safety goggles must be worn. In case of contact with eyes, rinse immediately with plenty of water. Spraying should only be carried out by professional users. Prolonged exposure of the eyes to a spray mist may cause temporary visual impairment. Avoid contact with the skin.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.