Woodchip wallpaper paste

Technical information sheet

200g / Item number 122002008 / EAN 4016215104200



A powdered, water-soluble woodchip wallpaper paste for safe and reliable pasting indoors. Easy to mix and simple to apply.

- Adhesive strength enhanced with polymers and methylcellulose
- Easily correctable
- 5 litres will be ready for use in 10 minutes
- enough for 5–6 rolls

Area of application

A powdered, water-soluble wallpaper paste for use with woodchip wallpaper, suitable for interior use.

Preparation

The substrate must be dry, sound, and free from dust and grease. Remove all traces of wallpaper, poorly adhering paint and distemper. Fill any holes and uneven areas with baufan products. Prime highly absorbent, sandy or chalky surfaces with baufan products. Pour the contents of the packet into 5 litres of cold, clean water whilst stirring vigorously, then continue stirring for a short while. Leave the mixture to stand for approx. 10 minutes, then stir thoroughly once more. Ready to use.

Processing

Apply the paste evenly to the wallpaper, fold it over and leave it to soak. Once the recommended soaking time has elapsed, hang the wallpaper edge-to-edge and press it down evenly and without leaving any air bubbles using a wallpapering brush, roller or spatula. It is essential to follow the wallpaper manufacturer’s instructions.

Notes

Please refer to the technical data sheet. Do not use at temperatures below +5 °C. Store out of the reach of children and in a dry place. Manufactured in Germany.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.