

- natural white
- for wipe-proof interior coatings
- preservative-free
- water vapour-permeable and breathable

Wall and Ceiling Distemper

Technical data to DIN EN 13330

Wet-scrub resistance:	Wipe-proof
Covering power:	Class 2 for 6 m ² /ltr
Gloss level:	Dead matt
Max. aggregate size:	Fine

Use

Distemper for indoor wall and ceiling surfaces.

Constituents

Calcium carbonate and cellulose ether

Substrate

For all mineral substrates (e.g. concrete, masonry, filling compounds, gypsum plaster, cement render and lime render), gypsum plasterboard and other drylining board, firmly adhering emulsion paint coats as well as woodchip and other wallpapers.

Substrate shall be dry, clean, strong, uniformly absorbent, and free from dust and grease. Remove loose material, existing wallpaper and distempers and badly adhering coatings from substrate. Prime highly absorbent, friable and chalking substrates with **baufan**[®] Deeply Penetrating Primer – solvent-free. Repair cracks, holes and irregularities with suitable **baufan**[®] filler.

Application

Stirring vigorously, briskly sprinkle pack contents into 2 ltr cold clean water and briefly continue to stir. Restir well after 2 hours. For best results, mixing of distemper on previous day to allow overnight swelling is recommended.

Distemper may be applied by roller, brush or wall brush. Application of second coat is recommended after first coat has fully dried in case of heavy colour variations in substrate.

Wash tools with water immediately after use.

Consumption

Smooth surfaces/
fine plaster aggregate → kg for approx. 15 m²

Exact consumption rate to be determined by trial application on site.

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Drying time

Approx. 5 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Tinting

With Universal Concentrated Colorants or Full-Tone and Tinting Paint.

Note

As **baufan**[®] Wall and Ceiling Distemper contains no preservatives, prepared product shall be applied within 2 days. To enhance wipe-proofness, **baufan**[®] Latex Binder may be added to prepared distemper – in such cases, water quantity shall be reduced by amount of binder added. Mask areas not to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking while using paint. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Please consult safety data sheet for safety-relevant data. Up-to-date safety data sheets are available from our website at www.baufan.de or from info@baufan.de.

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 60 months from production date (see batch label).

Item No.

099797	2.0 kg	Folding box
--------	--------	-------------

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.