

- scrub-resistant finish
- dries to transparent finish, silk gloss
- drip-inhibited, solvent- and plasticizer-free
- for enhancement of distempers and lime paints, for strengthening wallpaper adhesive

# Latex Binder

## Use

Binder serves as highly concentrated, water-thinnable additive for lime paints, distempers and wallpaper adhesives to improve bond strength and wipe-proofness. Also for overcoating wallpaper to achieve scrub-resistant finish. For indoor use.

## Constituents

Synthetic resin dispersion, water, additives

## Substrate

Substrate shall be dry, clean, strong and free from dust and grease. Remove loose material, existing wallpaper and badly adhering coatings from substrate. Prime highly absorbent, friable and chalking substrates with **baufan**<sup>®</sup> Deeply Penetrating Primer – solvent-free. Repair cracks, holes and irregularities with suitable **baufan**<sup>®</sup> filler.

## Application

**Additive for distempers and lime paints:** Reduce water quantity required for mixing paint/distemper by approx. 10 % and replace by equivalent amount of Latex Binder.

**Additive for wallpaper adhesive:** Stir approx. 20 % Latex Binder in ready-mixed wallpaper adhesive.

**Finish for wallpapers and the like:** Stir well prior to use and apply with roller, brush, wall brush or suitable spray equipment. For coating wallpapers, use in undiluted form. Wash tools with water immediately after use.

Not suitable for vinyl wallpapers and wallpapers with vinyl coating!

## Consumption

Sealer	→ from 150 ml/m <sup>2</sup>
Glue additive	→ approx. 750 ml/4 ltr glue
Paint/distemper additive	→ approx. 1 ltr/10 ltr paint/distemper

## Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

## Drying time

Approx. 5 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

## Note

Mask areas not to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Do not inhale spray mist. Refrain from eating, drinking and smoking while using paint. Wear goggles. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

## Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

GISCODE (German hazardous substances classification) for coating materials: BSW20

EU VOC limit value for this product:

(Cat.: A/h, Wb) = 30 g/ltr (2010)

Max. VOC content of this product: 1 g/ltr

## Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: see batch label.

## Item No.

100103	750 ml	PE pot
100127	2.5 ltr	PE tub
100141	5.0 ltr	PE tub
100165	10.0 ltr	PE tub

## Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.