

- dries to transparent finish
- silk gloss
- washable finish
- additive for distempers, for strengthening wallpaper adhesive

Latex Binder classic

Use

Serves as additive for lime paints, distempers and wallpaper adhesives to improve bond strength and wipe-proofness. Also for overcoating wallpaper to achieve washable finish.

Constituents

Synthetic resin dispersion, water, additives

Substrate

Substrate shall be dry, clean, strong, absorbent, and free from dust and grease. Remove loose material, existing wallpaper and badly adhering coatings from substrate. Prime highly absorbent, friable and chalking substrates with **baufan® Deeply Penetrating Primer** – solvent-free. Repair cracks, holes and irregularities with suitable **baufan®** filler.

Application

Additive for distempers: Reduce water quantity required for mixing paint/distemper by approx. 10 % and replace by equivalent amount of Latex Binder.

Additive for wallpaper adhesive: Stir approx. 20 % Latex Binder in ready-mixed wallpaper adhesive.

Finish for wallpapers and the like: Stir well prior to use and apply with roller, brush, wall brush or suitable spray equipment. For coating wallpapers, use in undiluted form. Wash tools with water immediately after use.

Not suitable for vinyl wallpapers and wallpapers with vinyl coating!

Consumption

Sealer	→ from 200 ml/m ²
Glue additive	→ approx. 750 ml/4 ltr glue
Paint/distemper additive	→ approx. 1 ltr/10 ltr paint

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Drying time

Approx. 5 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Note

Mask areas not to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Do not inhale spray mist. Refrain from eating, drinking and smoking while using paint. Wear goggles. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

GISCODE for coating materials: BSW20

EU VOC limit value for this product:

(Cat.: A/h, Wb) = 30 g/ltr (2010)

Max. VOC content of this product: 1 g/ltr

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: see batch label.

Item No.

100158	750 ml	PE pot
100172	2.5 ltr	PE tub
100189	5.0 ltr	PE tub
100196	10.0 ltr	PE tub

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.