



- supplied with brush
- for indoors, straightforward, neat application
- white, good hiding power

Direct White Touch-Up Paint

Technical data to DIN EN 13330

Wet-scrub resistance:	Class 2
Covering power:	Class 2 for 6 m ² /ltr
Gloss level:	Dead matt
Max. aggregate size:	Fine

Use

Emulsion paint for quickly touching up stains and scratches. Integrated brush allows straightforward, neat paint application directly from tube onto wall or ceiling.

Constituents

Synthetic resin dispersion, titanium dioxide, mineral fillers, water, additives

Substrate

Areas to be touched up shall be dry, clean and free from adhesion-impairing substances (e.g. grease, soap residue, dust). Scrape away loose material.

Application

Shake tube well prior to use. Remove screw cap. Press gently on tube to fill integrated brush with paint. Apply paint uniformly to area to be touched up.

If second application is required, repeat procedure after first coat has dried. After paint has fully dried, treated surface can accommodate usual loads.

Wash brush thoroughly with water after use.

Consumption

Smooth surfaces/fine plaster aggregate → approx. 1 m² per tube

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Drying time

Approx. 6-8 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Note

Mask areas not to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking while using paint. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction.

Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

GISCODE for coating materials: BSW20

EU VOC limit value for this product:

(Cat.: A/a, Wb) = 30 g/ltr (2010)

Max. VOC content of this product: 20 g/ltr

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 36 months from production date (see batch label).

Item No.

101988	250 g	Stand-up tube
--------	-------	---------------

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.