

- ready-tinted
- for personalized interior decoration
- solvent-free

Super Color

Technical data to DIN EN 13330

Wet-scrub resistance: Class 3
 Gloss level: Matt
 Max. aggregate size: Fine

Use

Super Color paints are ready-tinted emulsion paints for indoor wall and ceiling surfaces.

Constituents

Polymer dispersion, pigments, mineral fillers, water, additives

Substrate

For all mineral substrates (e.g. concrete, masonry, filling compounds, gypsum plaster, cement render and lime render), gypsum plasterboard and other drylining board, firmly adhering emulsion paint coats and woodchip wallpaper, glass fabrics and other overcoatable wallpaper and wall coverings.

Substrate shall be dry, clean, strong and free from dust and grease. Remove loose material, existing wallpaper and badly adhering coatings from substrate. Prime highly absorbent, friable and chalking substrates with **baufan®** Deeply Penetrating Primer – solvent-free. Repair cracks, holes and irregularities with suitable **baufan®** filler.

Application

Stir well prior to use and apply with roller, brush, wall brush or suitable spray equipment. As primer, paint may be diluted with max. 5 % water. Apply finishing coat in undiluted form after first coat has fully dried. Priming with **baufan®** Living Space White is recommended when applying colours Apricot, Sun, Cherry and Pistachio to dark, inhomogeneous substrates. When coating larger areas, always work with live edges to prevent laps (flashing). Wash tools with water immediately after use.

Notes on airless spray application

Spray angle: 50°
 Nozzle: 0.023 – 0.027
 Spraying pressure: 120 – 180 bar

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. For spray application, use combi-filter A2/P2.

Consumption per coat

Smooth surfaces/fine plaster aggregate → from 140 ml/m²

Exact consumption rate to be determined by trial application on site.

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Drying time

Approx. 5 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Note

In case of different batch numbers (imprint on lid), mix together batches prior to use. Depending on the paint used and substrate, colour deviations may arise. Mask areas not to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Do not inhale spray mist. Refrain from eating, drinking and smoking while using paint. Wear goggles. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal product (preservative):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

GISCODE (German hazardous substances classification) for coating materials: BSW20

EU VOC limit value for this product:
 (Cat.: A/a, Wb) = 30 g/ltr (2010)
 Max. VOC content of this product: 1 g/ltr

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: see batch label.

Colour	Container size	Order no.
Apricot	2.5 ltr	111246
Burgundy	2.5 ltr	111284
Cappuccino	2.5 ltr	111406
Citrus	2.5 ltr	111109
Lilac	2.5 ltr	111130
Blueberry	2.5 ltr	111345
Cherry	2.5 ltr	110355
Crocus	2.5 ltr	111185
Mango	2.5 ltr	111093
Chestnut	2.5 ltr	111222
Petrol	2.5 ltr	111307
Pine	2.5 ltr	111086
Pistachio	2.5 ltr	111383
Sun	2.5 ltr	111208
Terracotta	2.5 ltr	111116
Turquoise	2.5 ltr	111260

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.