

- synthetic resin-modified white filling compound
- for facades and damp spaces, for filling and smoothing
- white, high filling power, waterproof and frost-resistant

Outdoor Filler

Use

For overcoating uneven substrates, for filling cracks and holes in indoor and outdoor mineral walls and ceilings.

Constituents

Portland cement, synthetic resin dispersion powder, additives

Substrate

For application to concrete, aerated concrete, masonry, gypsum plaster, cement render and lime render, insulation, rigid foam and lightweight board. For mineral substrates only. Not suitable for application to glass, plastics and metal.

All substrates shall be dry, clean, level, strong, absorbent and free from adhesion-impairing substances. To increase strength, use **baufan® Deeply Penetrating Primer** – solvent-free. Completely remove any substrates that cannot be stabilized or that adhere inadequately. In case of doubt, perform trial application.

Application

Slowly sprinkle **baufan® Outdoor Filler** into clear water in clean mixing container and stir until pasty, lump-free compound is achieved. Mixing ratio for 1.0 kg **baufan® Outdoor Filler**: filling, coating – approx. 0.3 to 0.4 ltr water.

After mixing, allow to mature for approx. 1 minute, then restir. Prepared material is workable for approx. 4 hours and shall not be subsequently diluted. Apply with spatula, trowel or the like in any coat thickness. Wash tools with fresh water immediately after use.

Subsequent coating and bonding shall only be performed after filler-coated surface has fully dried. Observance of coating and adhesive manufacturers' instructions for pre-treatment of cementitious substrates is essential.

Consumption:

Per mm coat thickness → approx. 1.5 kg/m²

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Open time:

workable for approx. 4 – 5 hours

Drying time

Approx. 12 hours per mm coat thickness under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Note



Labelling: corrosive - danger. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. Keep out of reach of children. Avoid breathing dust. Wear protective gloves/protective clothing/eye protection. Do not get in eyes, on skin, or on clothing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. If on skin: Wash with plenty of water and soap. If medical advice is needed, have product container or label at hand. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains: Portland cement

GISCODE (German hazardous substances classification): ZP1 - low-chromate to TRGS 613

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 48 months from production date (see batch label).

Item No.

101346	1.0 kg	Folding box
101322	5.0 kg	Paper bag

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.