

- for carpets and PVC coverings
- easily removable with water
- reliable bonding, easy workability, ready-to-use, solvent- and plasticizer-free

# Floor Covering and Non-woven Fixative

## Use

Ready-to-use fixative for PVC and CV coverings as well as carpets with woven, non-woven, textile and foam backing. Coverings adhere reliably without bubbling and can be removed at a later date without damaging floor (particularly recommended for rental apartments). Suitable for spaces with floor heating systems and for loading by chair castors to DIN EN 12529.

## Constituents

Polymer dispersion, natural resin derivatives, mineral components, water, additives

## Substrate

Suitable for application to cement screeds, tiles, PVC coverings, V100 particleboard, waterproof-sealed parquet and similar moisture-resistant substrates.

Substrate shall be permanently dry, clean, level, strong, uniformly absorbent and free from dust and adhesion-impairing substances. Application of floor levelling compound is recommended for rough or uneven substrates. Pretreat highly absorbent, friable and porous substrates with **baufan® Deeply Penetrating Primer** – solvent-free. Covering to be fixed shall be acclimatized and stress-free, and shall lie flat.

## Application

Lay out floor covering, roughly cut to size and turn back one half. Apply fixative to substrate with short-pile roller or notched spatula (class A2 serration). After allowing required flash-off time, lay covering in material and press down uniformly. Flash-off time for absorbent substrates or vapour-permeable coverings is approx. 15 minutes; when laying impermeable coverings (e.g. PVC) on non-absorbent substrates, observe minimum flash-off time of 30 minutes. Then fix second half of floor covering in same way. If necessary, place ballast on edges and joints.

## Consumption

Approx. 200 - 250 g/m<sup>2</sup> - depending on application thickness and substrate

## Application temperature

+10 °C to + 30 °C for material, ambient air and substrate

## Removal of covering

When covering is peeled away at later date, fixative residue can be removed with water and **baufan Wallpaper Remover**. Allow solution to work for approx. 15 minutes, scrape off residue with plastic spatula, then wash down thoroughly with water.

## Note

Observance of covering manufacturer's laying guidelines is essential. Immediately remove fixative residue with water. Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking during application. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

## Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

## Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 48 months from production date (see batch label).

## Item No.

102763	3.0 kg	PE tub
102770	5.0 kg	PE tub
102787	10.0 kg	PE tub

## Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.