

- for indoor and outdoor use, highly vapour-permeable
- white, special adhesion-promoting primer
- solvent- and preservative-free

Decor and Plaster Primer

Use

Special adhesion-promoting primer for pretreatment of finely porous, absorbent to low-suction substrates. Produces finely textured base for subsequent coating with all finish plasters/renders for indoors and outdoors. Also for use as texturing wall paint. For wall and ceiling surfaces.

Constituents

Potassium water glass, synthetic resin dispersion, titanium dioxide, marble flour, marble aggregate (< 0.5 mm), water, additives

Substrate

For substrates such as concrete, cement and lime/cement render, masonry, gypsum substrates, fibre-cement board, absorbent, dispersion-bound plasters/renders and paint finishes.

Substrate shall be dry, clean, strong and free from dust and grease. Remove loose material, existing wallpaper and badly adhering coatings from substrate. Prime highly absorbent, friable and chalking substrates with **baufan® Deeply Penetrating Primer** – solvent-free. Repair cracks, holes and irregularities with suitable **baufan®** filler.

Application

Stir well prior to use and apply with roller or brush. If necessary, dilute with max. 5 % Silicate-Fixative. Ensure uniform coverage to prevent any colour differences in substrate from showing through. Wash tools with water immediately after use.

Surfaces already coated with **baufan® Decor and Plaster Primer** must not be treated with gypsum-based filling compounds. **baufan® Multi-Purpose Filler** is recommended in such cases.

Consumption per coat

Smooth surfaces/fine plaster aggregate → from 350 g/m²

Exact consumption rate to be determined by trial application on site.

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Drying time

Approx. 8 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Tinting

With max. 5% Universal Concentrated Colorant (LW (light- and weather-resistant) oxide types).

Matching of primer colour with subsequently applied product is recommended.

Note

Mask areas not to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Do not inhale spray mist. Refrain from eating, drinking and smoking while using paint. Wear goggles (not with glass). In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

GISCODE (German hazardous substances classification) for coating materials: BSW10

EU VOC limit value for this product:

(Cat.: A/h, Wb) = 30 g/ltr (2010)

Max. VOC content of this product: 15 g/ltr

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: see batch label.

Item No.

013168	5.0 ltr / 8.0 kg	PE tub
013175	10.0 ltr / 16.0 kg	PE tub

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.