



- crack-free curing, fibre-reinforced
- for indoor and outdoor use, ready-to-use
- easy to smooth, weatherproof

Facade and Damp Space Filler

Use

White, ready-to-use dispersion filling compound for indoor and outdoor wall and ceiling surfaces. It is excellently suited for patching smaller cracks and holes and for smoothing out irregularities. Ideal for damp and humid spaces (e.g. kitchens, bathrooms and garages) and for facades. Not suitable for filling works to wood, metal, glass and plastic.

Constituents

Synthetic resin dispersion, mineral fillers, water, additives

Substrate

For substrates such as concrete, plaster, render and masonry, emulsion paint coats and similar surfaces. Substrate shall be dry, strong and free from adhesion-impairing substances (e.g. dust, mould oil). Remove badly adhering coatings and loose plaster. Pretreat highly absorbent, friable and chalking substrates with **baufan®** Deeply Penetrating Primer – solvent-free.

Application

Knead tube well prior to use.

Apply filler with finishing trowel up to max. coat thickness of 5 mm. Irregularities can be smoothed down or felt-floated while filler is still damp. Subsequent coating and bonding shall only be performed after coated surface has fully dried.

Wash tools with water immediately after use.

Consumption

Per mm application thickness → approx. 1.7 kg/m²

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Drying time

Approx. 4-7 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking while using filler. Wear goggles. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 48 months from production date (see batch label).

Item No.

020333

400 g

PE tube

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.