

- for wood, coated surfaces and similar substrates
- white, ready-to-use, very good for sanding, for indoor use
- no subsequent working-over by roller, solvent-free, quick-drying

Fine Filler

Use

Filler for evening out minor irregularities indoors. Subsequent sanding produces ideal, coatable substrate.

Constituents

Synthetic resin dispersion, mineral fillers, water, additives

Substrate

For substrates such as plaster, render, concrete and gypsum plasterboard. Also for use on natural wood, particleboard, veneer/core plywood etc.

Substrate shall be dry, clean, strong and free from dust and grease. Remove loose material, existing wallpaper and badly adhering coatings from substrate. Prime highly absorbent, friable and chalking substrates with **baufan®** Deeply Penetrating Primer – solvent-free. In case of doubt, perform trial application.

Application

Knead tube well prior to use! Apply with spatula or trowel or directly from tube. Filler exhibits crack-free drying for up to 3 mm coat thickness. For greater thicknesses, apply in several coats, each new coat being applied only after previous coat has fully dried. Wash tools with water immediately after use.

Filler is easy to sand when fully dried.

Consumption per coat

Per mm coat thickness → approx. 1.8 kg/m²

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Drying time

Approx. 1-2 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking while using filler. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

GISCODE (German hazardous substances classification) BSW20

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 48 months from production date (see batch label).

Item No.

101063	400 g	PE tube
--------	-------	---------

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.