

- white, fibre-reinforced, universal application
- for indoor and outdoor use, solvent-free
- for wall and ceiling surfaces

Ready-Mix Filler

Use

Dispersion-based filler is ideal for patching, smoothing and finishing uneven, rough ceilings, walls and facades, and for reliable filling to precast-concrete units.

Constituents

Synthetic resin dispersion, mineral fillers, water, additives

Substrate

For substrates such as gypsum plaster, cement render and lime render. Also suitable for all mineral substrates (e.g. concrete, aerated concrete, clay bricks/blocks), emulsion paints and gypsum plasterboard. Not suitable for filling works to wood, metal, glass and plastic.

Substrate shall be dry, clean, strong and free from dust and grease. Remove loose material, existing wallpaper and badly adhering coatings from substrate. Pre-fill any deep holes, chips and spalls indoors with **baufan® Indoor Filler** or outdoors with **baufan® Outdoor Filler**. Prime highly absorbent, friable and chalking substrates with **baufan® Deeply Penetrating Primer** – solvent-free.

Application

Knead tube well prior to use. Apply with finishing trowel or spatula up to max. coat thickness of 5 mm. Where thicker application is required, additional filler can be applied after first coat has fully dried. Irregularities can be smoothed down while filler is still damp. Subsequent coating and bonding shall only be performed after filler-coated surface has fully dried. No priming is required for subsequent painting and wallpapering. Wash tools with water immediately after use.

Consumption per coat

Per mm application thickness → approx. 1.7 kg/m²

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Drying time

Approx. 5 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking while using paint. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

GISCODE (German hazardous substances classification) for coating materials: BSW20

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 48 months from production date (see batch label).

Item No.

101216	400 g	PE tube
--------	-------	---------

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.