

- odourless, solvent-free
- ready-for-use, milky-turbid (dries to transparent finish)
- easy workability, high initial adhesion

Glassfibre and Wall Covering Adhesive

Use:

For bonding wall and ceiling coverings indoors. Particularly suitable for glassfibre fabrics and glassfibre fabric wallpapers that are subsequently overcoated. Also for textile coverings, cork, fabric and foam vinyl wallpapers, rigid-foam lining papers as well as suede and PVC wallpapers. As adhesion promoter for wallpaper adhesive.

Constituents

Synthetic resin dispersion, water, additives

Substrate

Suitable substrates – Concrete, aerated concrete, gypsum wallboard, filling compounds, cement render, gypsum plaster, rigid-foam and wood-based panel products, existing emulsion paint coatings. Varnished substrates shall be scuff-sanded.

Substrate shall be dry, clean, strong, uniformly absorbent, and free from dust and grease. Remove loose material, existing wallpaper and badly adhering coatings from substrate. Prime highly absorbent, friable and chalking substrates with **baufan®** Deeply Penetrating Primer – solvent-free. In case of doubt, perform trial bonding. Repair cracks, holes and irregularities with suitable **baufan®** filler.

Application

Stir adhesive well prior to use. Cut glassfibre fabric or wallpaper to required length. Apply adhesive generously and uniformly to wall with lambskin roller over 1 – 3 strip width and allow flash-off time of a few minutes. Finally apply wallpaper to wall with hard rubber roller, taking care to prevent bubbles. Allow longer flash-off time in case of low-suction substrates, low temperatures or high humidity. Please observe wall covering manufacturer's application guidelines during all works. Immediately remove adhesive residue with fresh water. Wash tools with water immediately after use.

Wall and ceiling surfaces may be overcoated with suitable emulsion paints.

Consumption

Smooth surfaces → from 200 g/m²

Exact consumption rate to be determined by trial application on site.

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Open time

Approx. 20 minutes

Correction time

Max. 15 minutes

Drying time

Overcoatable after approx. 24 hours, under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking while using adhesive. Wear goggles. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: see batch label.

Item No.

102602	750 g	PE pot
102626	3.0 kg	PE tub
102633	16.0 kg	PE tub

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.