

- for all timber species, solvent-free
- dries to transparent finish
- also for use as handicraft adhesive

Cold Wood Glue

Use

Ready-to-use, solvent-free white glue for bonding wood, paper, cardboard and textiles. baufan® Cold Wood Glue dries to transparent finish. Joint remains elastic and is ageing-resistant.

Constituents

Synthetic polymer dispersion, water, additives

Substrate

For wood, textiles, leather, paper and cardboard. All components to be joined shall be clean, free from adhesion-impairing substances and properly fitting.

Application

Surfaces for bonding shall be dry, strong, and free from dust and grease. Apply baufan® Cold Wood Glue thinly to one of surfaces for bonding (for hardwood, end-grain or rough surfaces to both surfaces) and press together while still moist. Minimum pressing time is 15 minutes, for laminated wood board approx. 40 minutes. Glued joint is fully loadable after 24 hours.

Immediately remove surplus glue with cloth. Wash tools with water immediately after use.

Consumption

Depending on substrate and application thickness → from 110 g/m²

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Open time

Approx. 15 minutes

Drying time

Approx. 24 hours per mm coat thickness under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking during use. Wear goggles. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

GISBAU-GISCODE for laying materials: D1

Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 48 months from production date (see batch label).

Item No.

102404	250 g	Thin-tipped bottle
102428	500 g	Thin-tipped bottle
102442	1.0 kg	Thin-tipped bottle

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.