

- natural-coloured, ready-to-use
- for indoor and outdoor use
- odourless, tintable with full-tone paints



Wood Putty

Use

For filling and smoothing cracks, holes, joints, slots, damaged edges of windows, doors, steps, furniture and other wooden objects.

Constituents

Synthetic resin dispersion, wood fibres, mineral fillers, water, additives

Substrate

For timber substrates.

Substrate shall be dry, clean, level, strong, absorbent and free from adhesion-impairing substances. Completely remove any substrates that cannot be stabilized or that adhere inadequately. In case of doubt, perform trial application.

Application

Stir well prior to use. Apply with spatula, trowel or the like. Filler exhibits crack-free curing for up to 5 mm coat thickness. For greater thicknesses, apply in several coats, each new coat being applied only after previous coat has fully dried. Wash tools with water immediately after use. After full drying, Wood Putty is easy to work mechanically (sanding, drilling), to overpaint or to treat with decorative stain. Gentle scuff-sanding of surface is recommended prior to staining.

Consumption

Per mm coat thickness → approx. 1.4 kg/m²

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Drying time

Approx. 24 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Tinting

With max. 10 % suitable Universal Concentrated Colorants.

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking while using paint. Wear goggles. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

GISCODE for coating materials: BSW20

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: see batch label.

Item No.

101001	200 g	Metal can
101018	1.0 kg	Metal can

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.