

- white, for filling, smoothing and modelling
- for indoor use, trowellable to flat, level finish
- easy workability, stress-free

Indoor Filler

Use

Cellulose-reinforced, natural gypsum-based filling compound for indoor wall and ceiling surfaces. For overcoating uneven substrates and ideal for filling cracks and holes of any depth or width in walls and ceilings in dry spaces. For bonding rigid foam and solid gypsum board, for installing and anchoring brackets/supports.

Constituents

Gypsum, methyl cellulose

Substrate

For substrates such as concrete, aerated concrete, masonry, gypsum plaster, cement render and lime render, insulation, rigid foam and lightweight board. Not suitable for application to glass, plastics and metal. **baufan®** Outdoor Filler is recommended for external and moisture-exposed internal surfaces.

Substrate shall be dry, clean, strong, absorbent, and free from dust and grease. Remove loose material, existing wallpaper and badly adhering coatings from substrate. Prime highly absorbent, friable and chalking substrates with **baufan®** Deeply Penetrating Primer – solvent-free. In case of doubt, perform trial application.

Application

Slowly sprinkle Indoor Filler into clear water in clean mixing container and stir until pasty, lump-free compound is achieved. After mixing, allow to mature for approx. 3 minutes, then restir. Prepared material shall not be subsequently diluted! Apply with spatula, trowel or the like in any coat thickness. Wash tools with water immediately after use.

Mixing ratio for	1.0 kg	Filler:
Bonding, anchoring wall plugs, filling –		
	approx. 0.5 to 0.6 ltr water	
Smoothing, filling –	approx. 0.6 to 0.7 ltr water	

Prior to overcoating, prime full surface of wall and ceiling surfaces to avoid patchy finish.

Consumption

Per mm coat thickness → approx. 0.7 kg/m²

Working life

Up to approx. 1 hour

Setting

After approx. 2 hours

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Overcoatable

After approx. 24 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 60 months from production date (see batch label).

Item No.

101209	500 g	Folding box
101261	1.0 kg	Folding box
101247	5.0 kg	Paper sack
101285	10.0 kg	Paper sack
101292	25.0 kg	Paper sack

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.