

- universal application
- for indoor use, solvent-free
- for wood, stone, tiles and many plastics

Assembly Adhesive

Use

baufan[®] Assembly Adhesive is ideal for bonding skirtings, wood panels, polystyrene decorative panels and insulation board, mouldings, ceramic tiles, mosaic etc. Not suitable for bonding polyethylene, polypropylene, metallic materials and difficult-to-bond plastics.

Constituents

Copolymer dispersion, mineral components, water, additives

Substrate

Substrate shall be adequately absorbent, dry, strong and free from adhesion-impairing substances (e.g. grease, dust). Pretreat friable and chalking substrates with baufan[®] Deeply Penetrating Primer – solvent-free. If material for bonding is unable to absorb moisture, then substrate must be absorbent.

Application

Knead tube well prior to use. Apply dabs or continuous bead of baufan[®] Assembly Adhesive to components for assembling and press these down firmly. Secure heavy components in place until adhesive has cured. Immediately remove adhesive residue with fresh water.

Consumption

Depending on substrate and application thickness ► approx 300 – 500 g/m²

Tube contents suffice for approx. 12-20 m.

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Drying time

Approx. 24 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 48 months from production date (see batch label).

Item No.

102589	300 g	PE tube
--------	-------	---------

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.