



- high bond strength
- solvent-free
- for all wallpaper types

Seam Adhesive

Use

Ready-to-use dispersion adhesive is ideal for sticking down debonded (loose) wallpaper seams on all substrates.

Constituents

Synthetic polymer dispersion, water, additives

Substrate

Substrate shall be strong and free from dust.

Application

Knead tube well prior to use. Apply adhesive directly from tube to wallpaper or substrate, spread uniformly and press down loose wallpaper. Immediately remove adhesive residue with damp cloth. Wash tools with water after use.

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Drying time

Approx. 10-15 minutes under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 48 months from production date (see batch label).

Item No.

102657	60 g	PE tube
--------	------	---------

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.