

- extra-strong with extremely high penetration
- quickly and effortlessly removes multi-coated woodchip wallpaper and other heavy wallpapers
- high coverage, odourless

Wallpaper Power Remover

Use

baufan[®] Wallpaper Power Remover is ideal for trouble-free removal of paper-backed, textile and vinyl wallpapers as well as distemper finishes. Its extra-strong removing properties allow quick and easy stripping even of woodchip wallpapers that have been overpainted several times or similar difficult-to-remove wallpapers.

Constituents

Non-ionic surfactant, water and additives

Substrate

For paper-backed, textile and vinyl wallpapers and distemper finishes.

Application

Stir 250 ml baufan[®] Wallpaper Power Remover into 5 ltr water. For lightweight wallpapers, water dosage can be increased to 10.0 ltr. Dilute larger quantities in same ratio. Hot water will enhance performance. Apply solution generously with brush or suitable spray equipment (do not inhale spray mist) and allow to work for approx. 15 minutes. If necessary, repeat application. Softened wallpapers can then be easily stripped. Prior to treatment, roughen waterproof and coated wallpaper with needle roller or coarse sandpaper. To remove distemper finishes, apply baufan[®] Wallpaper Power Remover (diluted 1:60) to surface, allow to work for short time, then scrape off with spatula. Remove any residue by washing down. Power Remover is neutral. Stains can be easily removed with water. Subsequent bonding is not impaired. Wash tools with water.

Consumption

1.0 ltr suffices for approx. 150 – 200 m² (depending on dilution).

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Note

Keep out of reach of children. Ensure adequate ventilation during application. Do not inhale spray mist. Refrain from eating, drinking and smoking during use. Avoid contact with skin and eyes. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 60 months from production date (see batch label).

Item No.

| | | |
|--------|---------|-----------|
| 102299 | 1.0 ltr | PE bottle |
|--------|---------|-----------|

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.