

- perfectly matches ingrain/woodchip wallpaper texture
- for indoor use
- solvent-free

Woodchip Repair Filler

Use

Repair Filler is excellently suited for patching damaged woodchip wallpaper. Ideal for patching plug holes, cracks and similar damaged areas. Thanks to its texture, filling compound provides a perfect match for ingrain/woodchip wallpapers.

Constituents

Synthetic resin dispersion, mineral fillers, water, additives, wood fibre

Substrate

Substrate shall be dry, clean, strong and free from dust and grease. Remove loose material from substrate. Prime highly absorbent, friable and chalking substrates with baufan® Deeply Penetrating Primer – solvent-free. Pre-fill any deep holes, chips and spalls with baufan® Indoor Filler or baufan® Surface Filler. Stick down debonded woodchip wallpaper seams with baufan® Wallpaper Seam Adhesive.

Not suitable for filling works to wood, metal, glass and plastic.

Application

Knead tube well prior to use and apply filler directly from tube to damaged area. If necessary, create required surface texture with spatula or brush. When fully dried, treated surface can be overcoated. Wash tools with water immediately after use.

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Drying time

Approx. 1 hour under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Note

Mask areas not to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

Product Code: M-DF01

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: see batch label.

Item No.

020425	330 g	PE tube
--------	-------	---------

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.